

Reka Glue Gun Pneumatic

reka ■

TR 80.3 Cartridge Hot-Spray-System



Fig. TR 80.3 Cartridge Hot-Spray-System

Made in Germany

Subject to technical modifications

The TR 80.3 Cartridge Hot-Spray-System consists of the TR 80.3 Cartridge gun and the stand on which the gun may be deposited, with pressure regulator and manometer.

The TR 80.3 Cartridge Hot-Spray-System is capable of spraying melting glues contained in 310 ml aluminium cartridges.

The TR 80.3 Cartridge gun has considerable advantages: It works with 310 ml aluminium cartridges. The nozzle is screwed with the spray-adaptor on to the cartridge thus enabling quick cartridge change.

The TR 80.3 Cartridge gun can spray PUR melting glues. PUR melting glues distinguish themselves by an extremely high thermal stability.

The electronic temperature control is integrated into the handle for easy operation.

The electronic temperature control responds to the slightest deviation, thus providing for the optimum working temperature.

The regulator for the compressed air and the manometer scale are integrated into the stand. The precise adjustment of the compressed air ensures an optimum and accurate application of the adhesives.

Material air and spray air are separately adjusted. You may work without interruption since the spray air is heated in the gun, thus preventing the glue from cooling down during its application.

Thanks to the great variety of Reka accessories you can choose an appliance configuration adapted to your individual requirements.

Technical Data

	TR 80.3
Voltage	230 V (120 V on request)
Heating capacity	400 W
Air pressure for glue max.	approx. 90 psi/6 bars
Air control spray max.	approx. 90 psi/6 bars
Air consumption max.	100 l / min.
Temperature control	electronic
Temperature control range	approx. 100 – 185°C, infinitely variable
Overheat protection	temperature controller
Fuse	4 A
Heat-up time	3 – 10 min. *
Length of connections (stand to handgun)	4,5 m
Length of electric cord	4,0 m
Contents of aluminium cartridge	310 ml
Weight of handgun	1400 g
Stand with pressure regulator and manometer (incl. in scope of supply)	

* Depending on type of adhesive.

Accessories

Pneumatic foot switch

Stationary equipment

Balancer

Reka Klebetechnik GmbH & Co.KG
 Siemensstr. 6
 D-76344 Eggenstein
 Tel. +49 721 / 970 780
 Fax +49 721 / 705 069
 Internet: www.reka-klebetechnik.de
 Email: info@reka-klebetechnik.de